

400 SERIES

600 SERIES

700 SERIES

STANLEY®

FLOORING





WEAR RESISTANCE

Durable Supreme Guard UV Coating protects against daily scratches and keeps floors looking newer for longer.



WATERPROOF

100% waterproof core and surface resist spills and moisture for worry-free living.



ACOUSTIC SHIELD

Built-in sound absorption reduces footstep noise and creates a quieter, more comfortable home.

Five layers. One reliable floor.



 **SUPREME GUARD UV COATING**

 **WEAR-RESISTANT LAYER**

 **DECORATIVE WOOD FILM**

 **SPC CORE** (STONE PLASTIC COMPOSITE)

 **HIGH-DENSITY IXPE UNDERLAY**

TOTAL BUILD UP **6,5 mm**

TECHNICAL SPECIFICATIONS

Wear Layer	0,50 mm
Total Thickness	5 + 1,5 mm
Plank Size	228 x 1220 mm
Installation	i4F Drop-Lock Technology
Water Resistance	100% Waterproof
Surface Treatment	Supreme Guard UV Coating
Acoustic Performance	$\Delta L_w = 20$ dB
Underfloor Heating	Yes · max 27°C
Use Class (EN)	23 – 34
Warranty	Residential 25 yr Commercial 10 yr

CERTIFICATIONS & STANDARDS



EN 14041:2004/AC2006



9001:2015
14001:2015
45001:2018



Phthalate Free



SCAN THE QR CODE FOR
INSTALLATION &
USER GUIDES

400 SERIES

Warm, rustic oaks with natural character — four inviting shades for cosy, lived-in homes.



HARVEST OAK

CT401



BARN OAK

CT402



RURAL OAK

CT403



YARD OAK

CT405



400 SERIES

HARVEST OAK

CT401

TOTAL THICKNESS

5 + 1,5 mm

PLANK SIZE

228×1220 mm

WEAR LAYER

0,50 mm

SURFACE TEXTURE

Embossed in Register (EIR)



400 SERIES

BARN OAK

CT402

TOTAL THICKNESS

5 + 1,5 mm

PLANK SIZE

228×1220 mm

WEAR LAYER

0,50 mm

SURFACE TEXTURE

Embossed in Register (EIR)





400 SERIES

RURAL OAK

CT403

TOTAL THICKNESS

5 + 1,5 mm

PLANK SIZE

228×1220 mm

WEAR LAYER

0,50 mm

SURFACE TEXTURE

Embossed in Register (EIR)



Powered by Click&Lock® and DL™ DropLock®
PRODUCED UNDER LICENSE OF THE PATENTS LISTED @www.lf.com/patents



400 SERIES

YARD OAK

CT405

TOTAL THICKNESS

5 + 1,5 mm

PLANK SIZE

228×1220 mm

WEAR LAYER

0,50 mm

SURFACE TEXTURE

Embossed in Register (EIR)



Powered by Click&Lock® and DL™ DropLock®
PRODUCED UNDER LICENSE OF THE PATENTS LISTED @www.lf.com/patents

700 SERIES

Light, cool-toned oaks for calm, contemporary interiors — four refined shades, from the pale elegance of Opal Oak to the deep, sophisticated tone of Onyx Oak.



OPAL OAK

PS701



AZURE OAK

PS702



CRYSTAL OAK

PS703



ONYX OAK

PS704



700 SERIES

OPAL OAK

PS701

TOTAL THICKNESS

5 + 1,5 mm

PLANK SIZE

228×1220 mm

WEAR LAYER

0,50 mm

SURFACE TEXTURE

Embossed in Register (EIR)



Powered by Click&Fit® and 3-Strip Lock®
PRODUCED UNDER LICENSE OF THE PATENTS LISTED @www.iaf.com/solutions



700 SERIES

AZURE OAK

PS702

TOTAL THICKNESS

5 + 1,5 mm

PLANK SIZE

228×1220 mm

WEAR LAYER

0,50 mm

SURFACE TEXTURE

Embossed in Register (EIR)



Powered by Click&Fit® and 3-Strip Lock®
PRODUCED UNDER LICENSE OF THE PATENTS LISTED @www.iaf.com/solutions



700 SERIES

CRYSTAL OAK

PS703

TOTAL THICKNESS

5 + 1,5 mm

PLANK SIZE

228×1220 mm

WEAR LAYER

0,50 mm

SURFACE TEXTURE

Embossed in Register (EIR)



Powered by Click&Fit and 3L TripleLock®
PRODUCED UNDER LICENSE OF THE PATENTS LISTED @www.4f.com/patents



700 SERIES

ONYX OAK

PS704

TOTAL THICKNESS

5 + 1,5 mm

PLANK SIZE

228×1220 mm

WEAR LAYER

0,50 mm

SURFACE TEXTURE

Embossed in Register (EIR)



Powered by Click&Fit and 3L TripleLock®
PRODUCED UNDER LICENSE OF THE PATENTS LISTED @www.4f.com/patents

STANLEY® FLOORING

PACKAGING & PALLET INFORMATION

PACKAGE

1,95 m²

7 pieces / box

20,36 kg

PALLET

87,62 m²

45 boxes

956 kg

STANLEY® and the STANLEY logo are registered trademarks of Stanley Black & Decker Inc.
All rights reserved.

Imported and distributed by Area Floors · Kiesel Kleine Brogel 57, 3990 Peer, Belgium
www.areafloors.com.tr ·
For customer services please contact: 2helpu.com