

STANLEY®

FLOORING
Care guide and safety


WARNING AND SAFETY
Read fully before installation and use. Retain for future reference.

BEFORE YOU BEGIN




Read all instructions completely before installation and use. Keep packaging and small parts away from children — choking hazard.

TRANSPORT & STORAGE




Store boxes flat and level on a clean, dry surface — never on edge. Keep indoors and dry; protect from sunlight, moisture and frost. Transport horizontally.

SUBFLOOR




Must be clean, dry, flat and stable. Maximum unevenness 3 mm over 1 m (DIN 18202).
Remove dust, debris and grease. Subfloor moisture max 80% r.h. (75% if heated); cement screed max 2% CM.

UNDERFLOOR HEATING




Confirm compatibility before installation. Surface temperature must not exceed 27°C. Raise and lower the heating gradually.

i4F DROP-LOCK




Install using the i4F Drop-Lock method only; follow the STANLEY Installation Guide.
Do not force, hammer the profile, or glue the joints unless specified.

ACCLIMATISE 48H



Leave unopened boxes in the room of installation for 48 hours before fitting, at 18–25°C. Maintain room climate before, during and after installation.

EXPANSION GAP



Leave a 5 mm gap around the perimeter and all fixed objects; use spacers. Do not exceed the maximum uninterrupted area of 12 m × 8 m without a profile. See the STANLEY Installation Guide.

CUTTING / PPE



Cutting generates dust. Work in a ventilated area and wear eye protection and a dust mask.

STANLEY® FLOORING - EDITION 6/2026

i4F Drop-Lock Technologies

STANLEY® and the STANLEY logo are registered trademarks of Stanley Black & Decker Inc. and are used under licence. All rights reserved.


Imported and distributed by Area Floors, Kiezel Kleine Brogel 57, 3990 Peer, Belgium.
www.areafloors.com.tr/stanley

STANLEY®

FLOORING
Care guide and safety

USE AND SAFETY IN SERVICE

FURNITURE




Fit soft felt pads under furniture legs; replace when worn. Use wide, soft Type W castors for wheeled chairs.

ENTRANCE MATS



Place non-staining, non-rubber-backed mats at entrances to trap grit and moisture.

DON'T DRAG




Lift heavy or sharp items to move them. Dragging can scratch or dent the surface.

SPILLS



Wipe up spills promptly. Do not allow standing water at the plank edges.

SUNLIGHT



Prolonged direct UV may affect colour over time. Use blinds or curtains in strongly lit areas.

DISPOSAL



Dispose of product and packaging per local regulations. Recycling marks are shown on the box.

CLASSIFICATION & COMPLIANCE — PER PRODUCT FAMILY

	WOOD	STONE
SLIP RESISTANCE	DS	DS
REACTION TO FIRE	Bfl-s1	Bfl-s1
USE CLASS	23 / 34	23 / 34
RESIDUAL INDENTATION	≤ 0.10 mm / ≤ 0.10 mm	≤ 0.10 mm / ≤ 0.10 mm
CE / STANDARD	EN 14041:2004/AC:2006	EN 14041:2004/AC:2006
DECLARATION (DOP)	See label	See label
WEAR RESISTANCE	Class 34 / ≥ 7.000 cycles	Class 34 / ≥ 7.000 cycles
IMPACT SOUND REDUCTION	ΔLw = 20 dB	ΔLw = 20 dB

Standards — slip: EN 13893 · fire: EN 13501-1 · residual indentation: EN ISO 24343-1 · EN 16511:2023 / ISO 24338 · impact sound: EN ISO 10140-3 / EN ISO 717-2 · CE: EN 14041:2004/AC:2006.
DoP No. per family — see product label. Source: TDS Edition 6/2026.

Drop-Lock Technologies

STANLEY® and the STANLEY logo are registered trademarks of Stanley Black & Decker Inc. and are used under licence. All rights reserved.

Imported and distributed by Area Floors, Kiezel Kleine Brogel 57, 3990 Peer, Belgium. www.areafloors.com.tr/stanley

FLOORING
Care guide and safety

USE AND SAFETY IN SERVICE

SWEEP / VACUUM



Daily, as needed: sweep, dust-mop or vacuum (no beater bar) to remove grit and dust.

DAMP MOP



Weekly: damp-mop with a well-wrung mop and clean water or a pH-neutral cleaner. Damp, not wet.

DO

- Use entrance mats
- Fit felt pads under furniture
- Lift furniture instead of dragging
- Wipe spills promptly
- Keep a stable indoor climate

DON'T

- Use steam cleaners
- Use wax, polish or oil
- Use abrasives or solvents
- Flood the floor
- Lay rubber-backed mats on the floor

STAIN REMOVAL

ALWAYS TEST ANY CLEANING AGENT ON AN INCONSPICUOUS AREA FIRST.

STAIN TYPE	RECOMMENDED REMOVAL METHOD
DIRT, MUD, FOOD	Damp cloth + pH-neutral cleaner.
GREASE, OIL	Mild detergent solution, then rinse with a damp cloth.
INK, MARKER, LIPSTICK	Isopropyl alcohol on a soft cloth, then wipe clean.
SCUFF / SHOE MARKS	Soft cloth, light rubbing; pencil eraser for stubborn marks.
CANDLE WAX, CHEWING GUM	Harden with ice, lift gently with a plastic scraper.

LONG-TERM CARE

Re-check and replace felt pads and mats periodically. Keep expansion gaps free of debris.
Change underfloor-heating temperatures gradually between seasons.

STANLEY® FLOORING - EDITION 6/2026

Drop-Lock Technologies

STANLEY® and the STANLEY logo are registered trademarks of Stanley Black & Decker Inc. and are used under licence. All rights reserved.

Imported and distributed by Area Floors, Kiezel Kleine Brogel 57, 3990 Peer, Belgium.
www.areafloors.com.tr/stanley